



COLD STAR REFRIGERATED COMPOSITE



LIGHTER WEIGHT
TO HELP INCREASE
PAYLOAD



SEAMLESS EXTERIOR
PANELS OPTIMIZED FOR
GRAPHICS



CUSTOMIZABLE
TO YOUR
SPECIFICATIONS



IMPROVED
DURABILITY AND
LONGEVITY





COLD STAR REFRIGERATED COMPOSITE

FEATURES & BENEFITS

- › Improved Durability and Longevity with Body constructed of composite materials and aluminum in lieu of wood and steel. Improved corrosion resistance
- › Lighter weight than standard refrigerated bodies to help increase payload availability
- › **WALL CONSTRUCTION:** Insulated foam core panels, with foam core battens
- › **SUBFRAME:** Aluminum
- › **FLOOR:** Standard T Floor with option to upgrade to hat floor
- › Slip resistant, composite reinforced rear door threshold with thermal break
(Minimizes door threshold condensation)
- › **DOORS:** Optional overhead door or panel swing door
- › **REAR FRAME:** Stainless steel
- › **BUMPER:** 10" drop-step bumper
- › **ROOF:** Aluminum
- › **SCUFF:** 6" extended aluminum scuff with option to add additional scuff in 6" increments
- › **INTERIOR LINER:** Glass board
- › **EXTERIOR LIGHTING:** FMVSS 108 compliant

BODY SPECIFICATIONS

- › Body heights = 79"/85"
- › Body lengths = 12'/14'/16'
- › Body widths = 90"/96"
- › Applicable chassis apply

INSULATION FEATURES

- › **SIDEWALL:** 3" foam
- › **FRONT WALL:** 4" foam
- › **CEILING:** 3" foam
- › **FLOOR:** 3" foam between the sills



Products as shown may include optional equipment that is not part of the standard Morgan Truck Body configuration. Some product images may differ from current configurations and may not be available as depicted at the time of your order. NOTE: All dimensions, weights, and measurements specified herein are subject to Morgan's manufacturing tolerances, may change without notice, and may vary depending on options selected. Please contact your Morgan Representative for available options, complete up-to-date specifications and for measurements for your particular truck body and chassis specifications.

© Morgan Truck Body, July 2025